

MIN. $\frac{5}{8}$ " (16mm) CEMENT BOARD PANELS TO BE INSTALLED PRE-POUR AS FORM PANEL FOR CONCRETE CAP AT TOP OF WALL INSTALLED ON SLOPE TO MATCH ROOF PITCH

CAP FLASHING CLIPPED TO COUNTER FLASHING

ADDITIONAL FORM SUPPORT AT CEMENT BOARD PANELS IF REQUIRED

DIM 'A' AS SPECIFIED BY ENGINEERING PER APPLICABLE CODES

MINIMUM 6" (152mm) THICK CONTINUOUS CONCRETE CAP AT TOP OF WALL POURED INTEGRAL WITH FIREWALL OR AS PER LOCAL CODE

APPROVED FIRE TEMP. RATED ALUMINUM BURN CLIP AS SPECIFIED

COUNTER FLASHING & CLIP EDGE AS PER CODE SCREWED TO CEMENT BOARDS

ROOF SHEATHING & SHINGLES AS PER CODE

BASE FLASHING AS PER CODE

2x4" (38x89mm) CONT. TO MATCH ROOF SLOPE FASTENED THROUGH TO CAVITY (PRE-POUR)

$\frac{5}{8}$ " (16mm) TYPE 'X' GYPSUM BOARD FINISH IN ATTIC BOTH SIDES, TERMINATES AT CEMENT BOARD

REINFORCING AS PER DESIGN MINIMUM AS PER ULC LISTING W013

NUDURA 6" (152mm) STANDARD FORM UNIT

DISCLAIMER NOTICE:
SPECIFIC INFORMATION REQUIRED FOR COMPLIANCE WITH LOCAL CODES IS THE RESPONSIBILITY OF THE DESIGNER

The architecture, engineering, and design of the project using the Nudura products are the responsibility of the project's design professional. All products and systems must comply with local building codes and standards. This detail is for general information and guidance only and Nudura specifically disclaims any liability for the use of this detail. The project design professional determines, in its sole discretion, whether this detail or a functionally equivalent detail is best suited for the project. This detail is subject to change without notice. Contact Nudura to ensure you have the most recent version.

Fire Wall

Detail: Nudura 6" (152mm) Form Unit STC / Fire Wall Details
Firewall Projection Through Roof 2 Or 4 Hour Firewall

File Name:

FW6D5

Drawn by: T.V

Scale: 1 : 8

Date: 12/1/2021



Nudura Technical Support: 866-468-6299
International: +1 705-726-9499

tremcocpg.com



Construction Products Group